



**FLOOR PLAN**  
 1/4" = 1'-0"

**ELEVATION**  
 1/4" = 1'-0"

SOULVE FOOTINGS 3000  
 CONSTRUCTION TYPE VB  
 OCCUPANT LOAD 50  
 WIND LOAD (vert.) 90 LBS  
 (Exposure - B)

60L PLY MEMBRANE ROOFING  
 20 GA HIGH RIB STEEL  
 W/ASPH/FLT  
 CUTTER & DOWN  
 20 GA HIGH RIB STEEL SIDING  
 BY FABRIC  
 HVAC  
 SHIMMING TO MATCH-UP (Holes)

**GENERAL NOTES**

1. FOUNDATION AND/OR FUNDATION TO BE DETERMINED BY DATA IN INDICOM STATE PACKAGE.
2. SET OUT IN SECTIONS A1-90 OF APPROVED INDICOM STATE PACKAGE.
3. MATERIALS AND CONSTRUCTION TO CONFORM TO TABLES AND DATA ON SHEETS RF-5 THRU RF-9 OF THE INDICOM STATE PACKAGE.
4. SUPPORT COLUMN REQUIREMENTS & CONSTRUCTION TO CONFORM TO SHEETS RF-10 THRU RF-15 OF THE INDICOM STATE PACKAGE.
5. SHEARWALL LENGTH AND CONSTRUCTION DETERMINED BY DATA IN INDICOM STATE PACKAGE.
6. ROOF SLOPE TO BE 1/4" PER FOOT MINIMUM. ROOF HAS A TYPE 'A' CLASSIFICATION AS OUTLINED ON THE INDICOM STATE PACKAGE.

**NOTES**

1. THIS PLAN NOT AVAILABLE AT THIS TIME. BUILDING REQUIRED TO HAVE FIRE SEPARATION DISTANCE GREATER THAN 30 FT. IN ACCORDANCE W/ TABLE 608 OF THE BOO IBC.
2. PORTABLE FIRE EXTINGUISHERS TO BE SUPPLIED & INSTALLED IN ACCORDANCE W/ 1994 IFC AND CH. 10 OF THE BOO IBC.
3. PORTABLE FIRE EXTINGUISHERS TO BE PROVIDED ON SITE BY OWNER.
4. REMOVING TOILET OR BOTTLES WATER TO BE PROVIDED BY OWNER.
5. THIS PLAN TO BE LOCKED UP FOR HANDSET FOR 180° LINE OF THE UNIT 4' ABOVE BOTTOM TRIM.

